Overview

HP Chromebook 14 G7



Left

- 1. Microphones (2)
- 2. Webcam
- **3.** Privacy Camera (Optional)
- 4. Webcam LED

- 5. Touch Pad
- 6. SuperSpeed USB Type-A 5Gbps signaling rate
- **7.** HDMI v1.4
- 8. Nano Lock Slot (Lock sold separately.)

Overview



Right

- 1. Power Button
- 2. SuperSpeed USB Type-C® 5Gbps signaling rate (Power Delivery, video, data)
- 3. SuperSpeed USB Type-A 5Gbps signaling rate
- 4. MicroSD Memory Card Reader
- 5. Stereo Headphone / Microphone Combo Jack

Overview

AT A GLANCE

- Supports latest Intel[®] Celeron[®] N4500 and N5100 processors
- Choice of up to 8 GB memory and 64 GB eMMc storage
- Intel® Wi-Fi 6 AX 2x2 WLAN with MU-MIMO and HP Extended Range Wireless Lan for stable connection in dense environment
- Optional backlit keyboard
- Narrow bezel display design
- 180-degree hinge and optional IPS anti-glare touchscreen for collaboration
- Optional privacy camera
- All-day battery life
- Spend less time charging with HP Fast Charge technology
- One HDMI port to connect to displays and projectors without dongle
- 1 SuperSpeed USB Type-C® 5Gbps signaling rate (Power Delivery, video, data)
- 18.35mm Thin from the front
- Weight starting at 1.54 kg (3.38 lbs)
- Front-facing 720p HD camera comes with two microphones
- Android Apps ready

NOTE: See important legal disclosures for all listed specs in their respective features sections.



Technical Specifications

PRODUCT NAME

HP Chromebook 14 G7

OPERATING SYSTEM

Preinstalled Chrome OS

PROCESSORS

Intel® Celeron® N4500 (up to 2.8 GHz burst frequency, 4 MB L3 cache, 2 cores) ^{1,2} Intel® Celeron® N5100 (up to 2.80 GHz burst frequency, 4 MB L3 cache, 4 cores) ^{1,2}

Processor Family Intel® Celeron® processor (N5100, N4500)

- 1. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations Intel's numbering, branding and/.or namig is not a measurement of higher performance
- 2. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

CHIPSET

Chipset is integrated with processor



GRAPHICS

Integrated

Intel® UHD Graphics 3

Supports

Support HD decode, DX12, HDMI

3. FHD/HD content required to view HD images.

DISPLAY

Non-Touch

35.56 cm (14") diagonal, HD (1366 x 768) anti-glare WLED SVA, 250 nits, 45% NTSC, eDP NB ultraslim 3,4 35.56 cm (14") diagonal, FHD (1920 x 1080) anti-glare WLED UWVA, 250 nits, 45% NTSC, eDP NB slim 3,4 **Touch**

35.56 cm (14") diagonal, HD (1366 x 768) anti-glare WLED SVA, 250 nits, 45% NTSC, eDP NB Touch on panel 3,4,5 35.56 cm (14") diagonal, FHD (1920 x 1080) anti-glare WLED UWVA, 250 nits, 45% NTSC, eDP NB slim Touch on panel 3,4,5

- 3. FHD/HD content required to view FHD/HD images.
- 4. Resolutions are dependent upon monitor capability, and resolution and color depth settings.
- 5. Actual brightness will be lower with touchscreen or Sure View.

STORAGE AND DRIVES

Primary Storage

128 GB eMMC 5.0 ⁶

64 GB eMMC 5.0 6

32 GB eMMC 5.0 6

6. For storage drives, GB = 1 billion bytes. Actual formatted capacity is less. Up to 9 GB is not user available

MEMORY

Maximum Memory

8 GB LPDDR4X-4266 SDRAM

Memory

8 GB LPDDR4X -4266 SDRAM



Technical Specifications

4 GB LPDDR4X -4266 SDRAM

Memory Slots

Memory soldered on board

NETWORKING/COMMUNICATIONS

WIAN

Intel® Dual Band Wi-Fi 6 AX201 802.11a/b/g/n/ac/ax (2x2) WLAN and Bluetooth® 5.1 Combo, non-vPro® 7

MU-MIMO supported
HP Extended Range WLAN supported

Chromecast

Chromecast Support 8

- 7. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. The specifications for Wi-Fi 6 (802.11ax WLAN) are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ax WLAN devices. Only available in countries where 802.11ax is supported.
- 8. Chromecast must be purchased separately.

AUDIO/MULTIMEDIA

Audio

HD audio
Dual 2W stereo speakers
Integrated dual microphones

Camera

720p HD camera ⁹ Privacy shutter ¹⁰

- 9. HD content required to view HD images.
- 10. Privacy shutter is an optional feature.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

Full-size island-style Chrome keyboard, spill resistant



Technical Specifications

Full-size island-style Chrome keyboard, backlit, spill resistant 11

Pointing Device

Clickpad with multi-touch gesture support

Taps enabled as default

11. Backlit keyboard is an optional feature.

SOFTWARE AND SECURITY

Preinstalled Software

HP Classroom Manager 21

Manageability Features

Chrome Education Upgrade 22,23

Security Management

Titan C security chip

Nano Lock Slot (Lock sold separately.)

Zero Touch Enrollment

- 21. HP Classroom Manager is sold separately. Control and device locking from the teacher's desktop requires purchase of HP Classroom Manager.
- 22. Sold separately.
- 23. Chrome Education Upgrade requires one-time setup, subscription, Google Admin Console, and your organization's domain. Please see https://support.google.com/a/answer/60216.

POWER

Power Supply

HP Smart 45 W USB Type-C adapter

Primary Battery

HP Long Life 2-cell, 47 Wh Li-ion polymer ^{13,14} HP Fast Charge Technology (90% in 90 minutes) ¹⁵

Power Cord

3-wire plug - 1m

Battery Life

Up to 12 hours and 30 minutes²⁴



Technical Specifications

Battery Weight

0.42 lb 0.192 kg

- 13. Battery is internal and not replaceable by customer. Serviceable by warranty.
- 14. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.
- 15. Recharges the battery up to 90% within 90 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.
- 24. Testing conducted by HP using Google Chrome OS power_LoadTest. Battery life will vary and the maximum capacity of the battery will naturally decrease with time and usage. See http://www.chromium.org/chromium-os/testing/power-testing for test details. Full charge battery life will decrease after Adaptive Battery Optimizer activation.

WEIGHTS & DIMENSIONS

Product Weight

Starting at 3.38 lb ¹⁶ Starting at 1.54 kg ¹⁶

Product Dimensions (w x d x h)

12.85 x 8.93 x 0.72 in 32.65x 22.7 x 1.83 cm

16. Weight will vary by configuration. Does not include power adapter



Technical Specifications

PORTS/SLOTS

- 1 SuperSpeed USB Type-C® 5Gbps signaling rate (Power Delivery, video, data)
- 2 SuperSpeed USB Type-A 5Gbps signaling rate
- 1 Stereo headphone/microphone combo jack
- 1 HDMI v1.4 17

Expansion Slots

1 Micro SD multi-format digital media reader Supports SD, SDHC, SDXC

17. HDMI cable sold separately.

SERVICE AND SUPPORT

1-year limited warranty and 90-day software limited warranty options depending on country. Batteries have a default one-year limited warranty. Refer to http://www.hp.com/support/batterywarranty/ for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: http://www.hp.com/go/cpc. 18

18. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)USB-C® 45W adapter

Nominal Operating Voltage 15V

Average Operating Power <4.3w with PLT test

Integrated graphics Intel UHD Graphics 12EUs/24EUs

Max Operating Power Temperature < 45W

Operating 41° to 95° F (5° to 35° C)

Non-operating -4° to 140° F (-20° to 60° C)

Relative Humidity

Operating 10% to 90% Non-operating 5% to 95%

Shock

Operating 40 G, 2 ms, half-sine Non-operating 240 G, 2 ms, half-sine

Random Vibration

Operating 1.043 grms
Non-operating 3.5 grms

Altitude (unpressurized)

Operating -50 to 10,000 ft (-15 to 3,048 m)
Non-operating -50 to 40,000 ft (-15 to 12,192 m)

Planned Industry Standard Certifications

UL Yes
CSA No
FCC Compliance Yes

ENERGY STAR® ENERGY STAR® 8.0 19

EPEAT® Silver in United States ²⁰

ICES Yes Australia / Yes NZ A-Tick Compliance Yes CCCYes Japan VCCI Compliance No KC Yes **BSMI** Yes **CE Marking Compliance** Yes **BNCI or BELUS** No CIT Yes GOST Yes Saudi Arabian Compliance (ICCP) Yes **SABS** Yes

19. Configurations of the HP ChromeBook 14 G7 that are ENERGY STAR® qualified are identified as HP ChromeBook 14 G7 ENERGY STAR on HP websites and on http://www.energystar.gov.

No



UKRSERTCOMPUTER

Technical Specifications

20. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit http://www.epeat.net for more information.



Technical Specifications

DISPLAYS

1. Actual brightness will be lower with touchscreen or sure view.

Note: all specifications represent the typical specifications provided by hp's component manufacturers; actual performance may vary either higher or lower.

Panel LCD 14-in FHD (1920x1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP NWBZ slim

 Outline Dimensions (W x H x D)
 316.17 x 197.98 max.

 Active Area
 309.37 x 174.02

 Weight
 <285g max.</td>

 Diagonal Size
 14.0"

 Thickness
 3.0mm max.

 Interface
 eDP 1.2

Surface Treatment Anti-glare (AG)

Touch EnabledNoneContrast Ratio600:1Refresh Rate60HzBrightness250nit

Pixel Resolution 1920 x 1080 (FHD)

Format RGB
Backlight LED
Color Gamut Coverage 45%
Color Depth 6bit

Viewing Angle UWVA 85/85/85

Panel LCD 14-in FHD (1920x1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP TOP NWBZ slim Outline Dimensions (W x H x D) 316.17 x 198.07 max.

 Active Area
 309.37 x 174.02

 Weight
 <290g max.</td>

Diagonal Size 14.0"

Thickness 3.0mm (Panel Side) / 3.2mm (PCBA Side) max.

Interface eDP 1.2

Surface Treatment Anti-glare (AG)

Touch Enabled
Contrast Ratio
Refresh Rate
Yes
600:1 - AG
60Hz

Brightness¹ 250 nits

Pixel Resolution 1920 x 1080 (FHD)

Format RGB
Backlight LED
Color Gamut Coverage 45%
Color Depth 6bit

Viewing Angle UWVA 85/85/85



Panel LCD 14-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR TOP NWBZ flat

 Outline Dimensions (W x H x D)
 315.9*197.54

 Active Area
 309.4 x 173.95

 Weight
 290g Max

Diagonal Size 14."

Thickness 3.0mm (Panel Side) / 3.2mm (PCBA Side) max.

Interface eDP 1.2

Surface Treatment Anti-glare (AG)

Touch Enabled Yes

Contrast Ratio 400:1 - AG
Refresh Rate 60Hz
Brightness¹ 250 nits

Pixel Resolution 1366 x 768 (HD)

Format RGB
Backlight LED
Color Gamut Coverage 45%
Color Depth 6 bits

Viewing Angle SVA 45/45/15/30

Panel LCD 14-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP NWBZ ultraslim Outline Dimensions (W x H x D) 315.9+/-0.3 x 197.54 +/- 0.5

Active Area 309.4 x 173.95
Weight 285g Max
Diagonal Size 14."

Thickness 3.0mm max Interface eDP 1.2

Surface Treatment Anti-glare (AG)

Touch Enabled None
Contrast Ratio 300:1 - AG
Refresh Rate 60Hz
Brightness 250nits

Pixel Resolution 1366 x 768 (HD)

Format RGB
Backlight LED
Color Gamut Coverage 45%
Color Depth 6 bits

Viewing Angle SVA 45/45/15/30

Technical Specifications

STORAGE

eMMC 5.0 Drive Weight 0.2 g

Rotation speed 32 GB/64 GB/128 GB

Cache Buffer

Height 1.4 mm
Width 11.5x13 mm
Interface MMC protocol
Transfer Rate Up to 250 MB/s
Seek Time Up to 70 MB/s

Logical Blocks 32 GB (31,268,536,320 Bytes)/64 GB (62,537,072,640

Bytes)/ 128 GB (125,074,145,280)

Operating Temperature 0 to 70 **Security Features** HS400

For storage drives, GB = 1 billion bytes. Actual formatted capacity is less. Up to 9 GB is not user available



NETWORKING

Intel® Wi-Fi 6 AX201 and Wireless LAN Standards
Bluetooth® 5.1 (802.11ax

2x2, supporting gigabit data rate) (non-vPro)^{1,5}

IEEE 802.11n

IEEE 802.11ac

IEEE 802.11ac

IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v

Interoperability Features Wi-Fi 6 technology

Frequency Band 802.11b/g/n/ax

•2.402 – 2.482 GHz 802.11a/n/ac/ax •4.9 – 4.95 GHz (Japan)

•5.15 – 5.25 GHz •5.25 – 5.35 GHz •5.47 – 5.725 GHz

•5.825 - 5.850 GHz

Data Rates •802.11b: 1, 2, 5.5, 11 Mbps

•802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)

•802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, ,80MHz &

160MHz)

•802.11ax: MCS0 ~ MCS11, (1SS and 2SS) (20MHz, 40MHz, ,80MHz &

160MHz)

Modulation Direct Sequence Spread Spectrum

OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM

•IEEE compliant 64 / 128 bit WEP encryption for a/b/g mode only

AES-CCMP: 128 bit in hardware

•802.1x authentication

•WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.

WPA2 certificationIEEE 802.11iWAPI

Network Architecture

Models

Ad-hoc (Peer to Peer)

Infrastructure (Access Point Required)

Roaming IEEE 802.11 compliant roaming between access points

Output Power² • 802.11b: +18.5dBm minimum

802.11g: +17.5dBm minimum
802.11a: +18.5dBm minimum

802.11n HT20(2.4GHz): +15.5dBm minimum
802.11n HT40(2.4GHz): +14.5dBm minimum
802.11n HT20(5GHz): +15.5dBm minimum
802.11n HT40(5GHz): +14.5dBm minimum
802.11ac VHT80(5GHz): +11.5dBm minimum
802.11ac VHT160(5GHz): +11.5dBm minimum
802.11ax HT40(2.4GHz): +10dBm minimum
802.11ax VHT160(5GHz): +10dBm minimum

Power Consumption •Transmit mode 2.0 W

•Receive mode 1.6 W

Idle mode (PSP) 180 mW (WLAN Associated)Idle mode 50 mW (WLAN unassociated)

Connected Standby 10mW

•Radio disabled 8 mW

Power Management ACPI and PCI Express compliant power management

802.11 compliant power saving mode

Receiver Sensitivity⁴ •802.11b, 1Mbps: -93.5dBm maximum

•802.11b, 11Mbps: -84dBm maximum
•802.11a/g, 6Mbps: -86dBm maximum
•802.11a/g, 54Mbps: -72dBm maximum
•802.11n, MCS07: -67dBm maximum
•802.11n, MCS15: -64dBm maximum
•802.11ac, MCS0: -84dBm maximum
•802.11ac, MCS9: -59dBm maximum
•802.11ax, MCS11(HT40): -59dBm maximum

•802.11ax, MCS11(VHT160): -58.5dBm maximum

Antenna type High efficiency antenna with spatial diversity, mounted in the display

enclosure

Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications

Form Factor PCI-Express M.2 MiniCard with CNVi Interface

Dimensions 1. Type 2230 : 2.3 x 22.0 x 30.0 mm

2. Type 1216: 1.67 x 12.0 x 16.0 mm

Weight 1. Type 2230 : 2.8q

2. Type 126: 1.3g

Operating Voltage 3.3v +/- 9%

Temperature Operating 14° to 158° F (–10° to 70° C)

Non-operating -40° to 176° F (-40° to 80° C)

Humidity Operating 10% to 90% (non-condensing)

Non-operating 5% to 95% (non-condensing)

Altitude Operating 0 to 10,000 ft (3,048 m)

Non-operating 0 to 50,000 ft (15,240 m)

LED Activity LED Amber – Radio OFF; LED Off – Radio ON

Technical Specifications

Integrated Module with Bluetooth 5.1 Wireless Technology

Bluetooth Specification 4.0/4.1/4.2/5.0/5.1 Compliant

Frequency Band 2402 to 2480 MHz

Number of AvailableLegacy : 0~79 (1 MHz/CH)ChannelsBLE : 0~39 (2 MHz/CH)

Data Rates andLegacy: 3 Mbps data rate; throughput up to 2.17 Mbps **Throughput**BLE: 1 Mbps data rate; throughput up to 0.2 Mbps

Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice

channels

Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps

asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

Transmit Power The Bluetooth component shall operate as a Class II Bluetooth device with

a maximum transmit power of + 9.5 dBm for BR and EDR.

- 1. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 is backwards compatible with prior 802.11 specs. The specifications for Wi-Fi 6 (802.11ax) are draft and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ax devices. Only available in countries where 802.11ax is supported.
- 2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
- 3. Check latest software/driver release for updates on supported security features.
- 4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
- 5. Wi-Fi 5 or 6 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.



POWER

HP Smart 45 W USB Type-C adapter **Dimensions** 3.74 x 1.69 x 1.08 in (9.5 x 4.3 x 2.75 cm)

Weight 0.45 lbs (200g) max

(Not including power cord. Power cord varies by country.)

Input 100 to 240 VAC

Input Efficiency Average Efficiency of 25%, 50%, 75%, 100% load condition with

115Vac/230Vac Spec:

5V:81.5% 9V:86.7% 12V:87.41% 15V:87.8% 47~63Hz

Input frequency range

 Input AC current
 Max. 1.4 A at 90 Vac

 Output
 5V/9V/12V/15V

Output power 45W

DC output 5V/9V/12V/15V
Hold-up time 5v/9V/12V/15V

Output current limit <5.0A

Connector USB Type-C®

Operating temperature 32°F to 95°F (0°to 35°C)

Non-operating (storage)

temperature

-4°F to 185°F (-20° to 85°C)

Altitude 0 to 16,400 ft (0 to 5000m)

Humidity20% to 95%Storage Humidity10% to 95%

EMI and Safety Eg:

Certifications *CE Mark - full compliance with LVD and EMC directives

* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.

* MTBF - over 200,000 hours at 25°C ambient condition.



Technical Specifications

HP Long Life 2-cell, 47 Wh Li-ion polymer **Dimensions (H x W x L)** 5.2 x 240.8 x 76.4 mm (0.204 x 9.48 x 3 inch)

Weight 0.192 kg (0.42 lb)

Cells/Type 2cell Lithium-Ion Polymer cell / 4473A9

Energy

Voltage 8.8V Amp-hour capacity 6.150 Ah Watt-hour capacity 47.3 Wh

Temperature

Operating (Charging)32° to 113° F (0° to 45° C)Operating (Discharging)14° to 122° F (-10° to 60° C)

Fuel Gauge LEDWarranty **Optional Travel Battery**No

Available

COUNTRY OF ORIGIN

China



Options and Accessories (sold separately and availability may vary by country)

Category	Description	Part Number
Cases	HP Prelude Pro Recycled 15.6 Backpack	1X644AA,1X644UT,1X644ET
	HP Prelude Pro Recycled 15.6 Top Load	1X645AA,1X645UT,1X645ET
Docking	HP USB-C/A Universal Dock G2	5TW13AA, 5TW13UT, 5TW13ET
	HP USB-C Travel Hub G2	7PJ38AA
Input/Out put	HP Bluetooth Fingerprint Reader USB Mouse	4TS44AA, 4TS44UT, 4TS44ET
	HP Bluetooth Travel Bluetooth Mouse	6SP30AA, 6SP30UT, 6SP30ET
	HP Comfort Grip USB Wireless Mouse	H2L63AA, H2L63UT
	HP USB 320M Wired Mouse	9VA80AA, 9VA80UT,9VA80ET
	HP USB Laser 3 Button USB Mouse	H4B81AA, H4B81ET
	HP USB Premium USB Mouse	1JR32AA, 1JR32UT
	HP USB Premium Wireless Mouse	1JR31AA, 1JR31UT
	HP USB Travel USB Mouse	G1K28AA, G1K28ET
	HP Wireless 2.4GHz X4000 Bluetooth Mouse	H3T50AA, H3T50UT
	HP WL USB Agnes Keyboard	T6U20AA, T6U20UT
	HP Slim Wireless Keyboard and Mouse	T6L04AA, T6L04UT
	HP Wireless USB Premium Keyboard	Z9N41AA, Z9N41AT
	HP Wireless Rechargeable 950MK Mouse and Keyboard	3M165AA, 3M165UT
	HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA, 9SR36UT,9SR36ET
	HP 235 WL Mouse and Keyboard Combo	1Y4DOAA, 1Y4DOUT
	HP 125 Wired Keyboard	266C9AA, 266C9UT
	HP 225 Wired Mouse and Keyboard Combo	286J4AA, 286J4UT
	HP HDMI to DVI Adapter	F5A28AA
	HP HDMI to VGA Adapter	H4F02AA, H4F02UT, H4F02ET
	HP USB-C to HDMI 2.0 Adapter	2PC54AA, 1WC36UT, 1WC36AA
	HP USB-C to RJ45 Adapter	V8Y76AA, V7W66AA, V7W66UT
	HP USB-C to USB 3.0 Adapter	N2Z63AA, N2Z63UT
	HP USB-C to VGA Adapter	P7Z54AA, N9K76AA, N9K76UT
Power	HP 45W USB-C® G2 AC Power Adapter	1HE07AA
	HP 45W USB-C® LC AC Power Adapter	1MZ01AA
	HP 65W USB-C® AC Power Adapter	1HE08AA
	HP 65W USB-C® Slim Travel AC Power Adapter	X7W50AA, 3PN48AA, 3PN48UT
Security	HP Nano Cable Lock	1AJ39AA,1AJ39UT
	HP SureKey Standard/Nano/Wedge Cable Lock	6UW42AA,6UW42UT
UCC	HP Stereo 3.5mm Headset	T1A66AA
	HP Wired USB-A Stereo Headset	T1A67AA



Summary of Changes

Date of change:	Version History:	Updated	Description of change:
March 10, 2021	V1 to V2	Add	Battery Life
March 31, 2021	V2 to V3	Updated	Bluetooth version
August 3, 2021	V3 to V4	Add	Zero Touch Enrollment in Security Management

Copyright © 2021 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. DisplayPort[™] and the DisplayPort[™] logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. © 2021 Google LLC All rights reserved. Google and the Google Logo are registered trademarks of Google LLC.

